



Ring saw HRE410

Depth of cut up to 300 mm



Ideal cutting performance due to a 6.5 kW P2® motor in conjunction with TYROLIT ring saw blades



Intelligent ergonomics – handle can be rotated 90° for horizontal cuts



Modular use with WSE1621 wall saw system or electric control unit PPE6

The HRE410 is an electric hand saw for wall and floor cuts to a depth of 300 mm. The ring saw is an ideal supplement to the WSE1621 wall saw system, enabling work without overcuts and therefore provides a

better alternative to corner drilling or diamond chain saws. The combination of a powerful 6.5 kW P2® motor and TYROLIT ring saw blades ensures exceptional cutting performance – for fast, precise

work. The intelligent ergonomics are another feature of this machine; the rear and front handle can be adjusted to enable an ideal position for cutting with less fatigue.



System & Accessories



Technical data

Saw blade

Max. depth of cut	300 mm
Max. ring saw blade Ø	410 mm

Drive

High-frequency motor

Power	6.5 kW
Speed	1938 rpm
Cooling	Water

Design

Modular use with WSE1621

P2® high-frequency technology

Adjustable, ergonomic handles

Front handle for left- and right-handed users

Rear handle can be rotated 90°

Water intake can be controlled directly on handle

IP 55 protection class

Overload and excess temperature display

Dimensions & weight

Length	505 mm
Width	320 mm
Height	520 mm
Weight	14.5 kg

System & Accessories

Ring saw HRE410/Electric control WSE1621

10999300	Ring saw HRE410
11002700	Electric control WSE1621 400V
11002643	Transport case HRE410

Ring saw HRE410/Electric control PPE6

10999300	Ring saw HRE410
11000500	Electric control PPE6 400V 10A IP65 12.5kg
11002643	Transport case HRE410

34438701 Ring saw blade RSL-FC (C1W 406x3.9x320)

34506869 Ring saw blade RSL (C1W 406x4.2x320)

11002010 Drive wheel